



TRIO SPLIT mission PRO WANDMODEL



Follow Me



2-Way
Draining



R32
Refrigerant



Louver Position
Memory



3D Air-Flow



Mono &
Multi



24h-Timer



Anti-Cold
Air Function



8°C Heating



Refrigerant
Leakage Detect



Bill Control



GA Stepless
Comfort
Technology



Turbo



Healthy Filters



Low Ambient
Cooling



Remote
Control



Emergency Using



1W Standby



Sleep-Mode



Auto Restart
Function



Remote
Control App

TRIO SPLIT mission PRO WANDMODEL

Super DC inverter



SETNAAM		MISSION-PRO-TRIO-81-R32	MISSION-PRO-TRIO-89-R32
BINNENUNIT 1		MISSION-PRO-27IU	MISSION-PRO-27IU
BINNENUNIT 2		MISSION-PRO-27IU	MISSION-PRO-27IU
BINNENUNIT 3		MISSION-PRO-27IU	MISSION-PRO-35IU
BUITENUNIT		M30-27FN8-Q	M30-27FN8-Q
CAPACITEIT			
Totale Koelcapaciteit	kW	7,91 (2,05-7,91)	7,91 (2,05-7,91)
Koelcapaciteit per binnendeel	kW	2,6 + 2,6 + 2,6	2,6 + 2,6 + 3,5
SEER	W/W	6,5	6,5
Energieklasse koeling		A++	A++
Verwarmingscapaciteit	kW	8,21 (2,34-8,21)	8,21 (2,34-8,21)
SCOP	W/W	4,0	4,0
Energieklasse verwarming (H/A)		A+	A+
SCOP	W/W	5,6	5,6
Energieklasse verwarming (H/W)		A++	A++
Luchtstroom binnenunit L/M/H	m³/h	240/370/440 + 240/370/440 + 240/370/440	240/370/440 + 240/370/440 + 270/440/500
Luchtstroom buitenunit	m³/h	2700	2700
ELEKTRICITEIT			
Voeding		220-240V / 50HZ / 1Ph	220-240V / 50HZ / 1Ph
Afzekerwaarde (traag)	A	16 traag	16 traag
Voedingskabel	mm²	3x2,5	3x2,5
Stuurkabel	mm²	4x1,5	4x1,5
Opgenomen vermogen koelen	W	750-1700	750-1700
Opgenomen vermogen verwarmen	W	720-1750	720-1750
Bedrijfsstroom	A	3,2-7,7	3,2-7,7
Bedrijfsstroom max	A	15	15
GELUID			
Geluidsdruk binnenunit S/L/M/H op 1m.	dB(A)	19/24/31/39 + 19/24/31/39 + 19/24/31/39	19/24/31/39 + 19/24/31/39 + 19/24/32/40
Geluidsdruk buitenunit	dB(A)	56	59
AFMETINGEN EN GEWICHTEN BINNENUNIT			
Afmeting (BxDxH)	mm	810x200x300 + 810x200x300 + 810x200x300	810x200x300 + 810x200x300 + 810x200x300
Gewicht	kg	7,4 + 7,4 + 7,4	7,4 + 8,3 + 8,3
AFMETINGEN EN GEWICHTEN BUITENUNIT			
Afmeting (BxDxH)	mm	800x333x554	800x333x554
Gewicht	kg	36	36
KOUDEMIDDELCIRCUIT			
Type/GWP		R32/675	R32/675
Vulling/voorgevuld tot/bijvulling	kg / m / g/m	1,57 / 15m / 12	1,57 / 15m / 12
Diameter vloeistof-/gasleiding	inch	1/4"x 3/8" + 1/4"x 3/8" + 1/4"x 3/8"	1/4"x 3/8" + 1/4"x 3/8" + 1/4"x 3/8"
Max. leidinglengte Totaal	m	60	60
Max. Leidinglengte per binnenunit	m	30	30
Max. hoogteverschil binnen- en buitenunit	m	15	15
Max. hoogteverschil tussen binnenunits	m	10	10
BEDIENING			
Infrarood afstandsbediening		RG58F(2H)BGED	RG58F(2H)BGED
WERKGEBIED			
Werkgebied koelen	°C	-15 - +50	-15 - +50
Werkgebied verwarmen	°C	-15 - +24	-15 - +24